MINNEAPOLIS DEP CON
SOUTH/EAST 124.7 284.7
NORTH/WEST 125.75 284.7
D-ATIS DEP
120.8
CLNC DEL
133.2
CPDLC
MINNEAPOLIS TOWER
123.95 273.55 (12L-30R)
126.7 273.55 (12R-30L, 4-22)
123.675 273.55 (17-35)

RADAR required.

TOP ALTITUDE: ASSIGNED BY ATC

Rwys 30L/R
Assigned headings 220° CW 360°
3500

MINNEAPOLIS
115.3 MSP
Chan 100

MSP 7

Rwy 17
Assigned headings 230° CW 285°
3500

R-208

MSP 7

Rwys 12L/R
Assigned headings 060° CW 100°
3500

208°

(20)

JURNY

R-258

FARMINGTON
115.7 FGT
Chan 104

(13)

(33)

RUMLE

R-318

(15)

(48)

PEDLN
9000 (MRA)

R-268

HALFWAY
111.2 FOW
Chan 49

(37)

(85)

TAKEOFF MINIMUMS
Rwys 12R, 17, 22: Standard.
Rwy 4: Standard with minimum climb of 202′ per NM to 2400.
Rwy 12L: Standard with minimum climb of 277′ per NM to 1100.
Rwy 30L: Standard with minimum climb of 208′ per NM to 2000.
Rwy 30R: Standard with minimum climb of 217′ per NM to 2000.
Rwy 35: Standard with minimum climb of 219′ per NM to 2000.

ORSKY
9000 (MRA)

9000
*2600
208°
(26)

R-306

ONTIJ
12000 (MRA)

(111)

R-278

MASON CITY
114.9 MCW
Chan 96

R-015

OMAHA
116.3 OVR
Chan 110

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

NC-1, 06 AUG 2026 to 03 SEP 2026
NC-1, 06 AUG 2026 to 03 SEP 2026