LOC/DME I-ANC	APP CRS		7R	7L
111.3	074°	Rwy Ldg	12400	10600
Chan 50		TDZE	132	128
		Apt Elev	151	151

AL-1500 (FAA)

ILS or LOC RWY 7R

TED STEVENS ANCHORAGE INTL (ANC) (PANC)

DME required.

T A -21°C

For inop ALS, increase S-ILS 7R Cat E visibility to RVR 4000, S-LOC 7R Cat E visibility to RVR 6000, and Sidestep Rwy 7L Cat E visibility to 2 SM. Rwy 7L threshold 6140 feet east of Rwy 7R threshold.

ALSF-2 Rwy 7R (A)

MALSR Rwy 7L (A5)

MISSED APPROACH: Climb to 780 then climbing right turn to 3000 on heading 230° and on TED VOR/DME R-210 to JUKEP/TED 15 DME and hold. (TACAN aircraft climb to 780 then climbing right turn to 3000 on heading 230° and EDF TACAN R-210 to JUKEP/EDF 22.6 DME and hold).

D-ATIS	ANCHORAGE APP CON	ANCHORAGE TOWER	GND CON
135.5	118.6 290.5	118.3 257.8	121.9 338.25





CATEGORY	A	B	C	D	E
S-ILS 7R	332/18 200 (200-½)				
S-LOC 7R	520/24 388 (400-½)		520/35 388 (400-⅝)		
SIDESTEP 7L	520/55 392 (400-1)			520-1½ 392 (400-1½)	
CIRCLING	700-1 549 (600-1)		800-1¾ 649 (700-1¾)	920-2½ 769 (800-2½)	920-2¾ 769 (800-2¾)

ELEV 151 D

TDZE 7R	132
TDZE 7L	128



HIRL all rwys
REIL Rwy 33
TDZL/RCLS Rwys 7L and 7R

AK, 09 JUL 2026 to 03 SEP 2026
AK, 09 JUL 2026 to 03 SEP 2026