SOCAL DEP CON
125.2 323.275
D-ATIS DEP
135.65
CLNC DEL
120.35 327.0
CPDLC
GND CON
(N) 121.65 327.0
(S) 121.75 327.0
(W) 121.4 327.0
LOS ANGELES TOWER
(N) 133.9 239.3
(S) 120.95 379.1
TAKEOFF MINIMUMS
Rwys 6L/R, 7L/R: NA-ATC.
Rwys 24L/R, 25L/R: Standard with minimum climb of 500' per NM to 640.
NOTE: DME/DME/IRU or GPS required.
NOTE: RADAR required.
NOTE: RNAV 1.
NOTE: Turbojets only.
NOTE: Maintain at or below 250K unless otherwise directed by ATC.
N
TOP ALTITUDE: 10000
SAN MARCUS RZS
10000 288° (24)
SCHOR
10000 288° (9)
KWANG
10000 273° (16)
WGGNR
10000 289° (11)
IKAYE
10000 342° (10)
FIXIT
10000 290K
289° (7)
MUELR
253° (11)
NAANC
253° (7)
ENNEY
5000
1300
257° (12)
MKGEE
252° (6)
EVOSE
5000
1300
(2) 253°
256° (2)
FABRA
3000
640
251°
DLREY
3000
640
251°
252° (2)
DOCKR
3000
640
251°
256° (2)
HIIPR
3000
640
251°
(CONTINUED ON FOLLOWING PAGE)
NOTE: Chart not to scale.