OSHNN ONE DEPARTURE (RNAV)

(OSHNN1.OSHNN) 17JUN21

LOS ANGELES, CALIFORNIA
LOS ANGELES INTL (LAX)

SOCAL DEP CON
124.3 363.2
D-ATIS DEP
135.65
CLNC DEL
120.35 327.0
CPDLC
GND CON
(N) 121.65 327.0
(S) 121.75 327.0
(W) 121.4 327.0
LOS ANGELES TOWER
(N) 133.9 239.3
(S) 120.95 379.1

TOP ALTITUDE: 17000

TAKEOFF MINIMUMS
Rwys 6L/R, 7L/R: NA-ATC.
Rwys 24L/R, 25L/R: Standard with minimum climb of 500′ per NM to 640.



NOTE: DME/DME/IRU or GPS required.
NOTE: RNAV 1.
NOTE: RADAR required.
NOTE: This departure to be used only if unable to use the ORCKA DEPARTURE.
NOTE: Rwys 24L/R departure expect RADAR vector to PEVEE prior to NAANC.
NOTE: Turn at HIIPR and DOCKR are required for ATC separation.
NOTE: MISEN TRANSITION restricted to aircraft landing LAS terminal area.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

(OSHNN1.OSHNN) 25331

OSHNN ONE DEPARTURE (RNAV)

AL-237 (FAA)

LOS ANGELES INTL (LAX)
LOS ANGELES, CALIFORNIA