ILS or LOC RWY 14

ROGUE VALLEY INTL/MEDFORD (MFR)

LOC/DME I-MFR	APP CRS	Rwy Ldg	8800
110.3	143°	TDZE	1303
Chan 40		Apt Elev	1335

DME required. DME or RADAR required for procedure entry.

T A -2°C Circling NA for Cats C and D northeast of Rwy 14-32. When Medford altimeter setting not received, procedure NA. For inop ALS, increase S-ILS 14 visibility to 1¾ SM, increase S-LOC 14# Cats C and D visibility to RVR 5500, increase S-LOC 14 Cats C and D visibility to 2½ SM.

MALSR

MISSED APPROACH: Climb to 6600 on I-MFR SE course to JILOK/I-MFR 1.6 DME and climbing right turn on heading 350° and on OED VORTAC R-160 to OED VORTAC and hold, continue climb-in-hold to 6600. #Missed approach requires minimum climb of 331 feet per NM to 4100.

ATIS	CASCADE APP CON*	MEDFORD TOWER*	GND CON	UNICOM
127.25	124.3 379.9	119.4 (CTAF) L 257.8	121.8	122.95





CL Rwy 14-32 L
TDZ/CL Rwy 14 L
REIL Rwy 32 L
HIRL Rwy 14-32 L



CATEGORY	A	B	C	D
S-ILS 14#		1503/18	200 (200-½)	
S-ILS 14		1929-1⅜	626 (600-1⅜)	
S-LOC 14#	1680/24	377 (400-½)	1680/35	377 (400-⅝)
S-LOC 14	2080/24 *777 (800-½)*	2080/40 *777 (800-¾)*	2080-1¾	*777 (800-1¾)*
CIRCLING	2080-1 *745 (800-1)*	2080-1¼ *745 (800-1¼)*	2080-2½ *745 (800-2½)*	2340-3 1005 (1100-3)

NW-1, 03 SEP 2026 to 01 OCT 2026
NW-1, 03 SEP 2026 to 01 OCT 2026