RNAV 1 - DME/DME/IRU or GPS.
RADAR required for non-GPS equipped aircraft.
TOP ALTITUDE: 5000
TAKEOFF MINIMUMS:
Rwy 4L, 14, 15L, 32, 33R: NA-ATC.
Rwy 4R: Standard with minimum climb of 500'/NM to 520.
Rwy 9: Standard with minimum climb of 500'/NM to 520.
Rwy 15R: Standard with minimum climb of 500'/NM to 520.
Rwy 22L: 300-1 with minimum climb of 500'/NM to 520, or standard with minimum climb of 500'/NM to 520 if tower reports no tall vessels in the departure area.
Rwy 22R: Standard with minimum climb of 500'/NM to 520.
Rwy 27: Standard with a minimum climb of 500'/NM to 1300.
Rwy 33L: Standard with a minimum climb of 500'/NM to 520.
NOTE: Jet aircraft only.
BOSTON DEP CON 133.0
D-ATIS 135.0
CLNC DEL 121.65 257.8
CPDLC
GND CON 121.75 121.9
BOSTON TOWER 128.8 257.8 (WEST) 132.225 257.8 (EAST)
BOS 25 NM
2500
N
HURBE 4000
CLAWW 4000 250K
ORRRR
FENWY
JAITE
GLLET
BRRRO 3000 250K
CHWDH
STEEM
WYMTH
HEWMO 5000 260K
NHANT
TASKT
TJAYY 1200 210K
DEDHM
KENWI
TEKKK
EXXXX
KIRAA
BLZZR
SPENO
CHESTER CTR
BARNES BAF
NELIE
NOTE: Chart not to scale.
(NARRATIVE ON FOLLOWING PAGE)