LOC/DME I-RJG	APP CRS	Rwy Ldg	7800
110.75	258°	TDZE	1126
Chan 44 (Y)		Apt Elev	1135

ILS or LOC RWY 25L

PHOENIX SKY HARBOR INTL (PHX)

Autopilot coupled approach NA below 1925.
Simultaneous approach authorized with Rwy 26.

MALSR

MISSED APPROACH: Climb to 3000 then climbing left turn to 5000 on heading 130° and PXR R-163 to POPKE/15 DME and hold.

D-ATIS	PHOENIX APP CON	PHOENIX TOWER	GND CON
127.575	128.65 353.9	118.7 278.8 (8-26) 120.9 254.3 (7L-25R, 7R-25L)	119.75 269.2 (N) 132.55 269.2 (S)

DME or RADAR REQUIRED



ELEV 1135 D TDZE 1126

3000 | 5000 hdg 130° | PXR R-163 | POPKE

*LOC only

Use I-RJG DME when on the localizer course.





HIRL Rwys 8-26, 7L-25R and 7R-25L
REIL Rwy 26

CATEGORY	A	B	C	D
S-ILS 25L	1326-½ 200 (200-½)			
S-LOC 25L	1520-½ 394 (400-½)			1520-¾ 394 (400-¾)
CIRCLING	1740-1 605 (700-1)		2040-2¾ 905 (1000-2¾)	2560-3 1425 (1500-3)

FAF to MAP 5.6 NM

Knots	60	90	120	150	180
Min:Sec	5:36	3:44	2:48	2:14	1:52

SW-4, 29 OCT 2026 to 26 NOV 2026
SW-4, 29 OCT 2026 to 26 NOV 2026