WAAS	APP CRS	Rwy Ldg	12000
CH 53419	353°	TDZE	5434
W35A		Apt Elev	5434

RNAV (GPS) Y RWY 35L

DENVER INTL (DEN)

RNP APCH - GPS.

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -26°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4000, increase LNAV visibility Cat C and Cat D to RVR 5500. LNAV procedure NA during simultaneous operations. Simultaneous approach authorized. Use of FD or AP required during simultaneous operations.

ALSF-2

MISSED APPROACH: Climb to 10000 direct MAXPU and on track 360° to GLL VOR/DME and hold.

D-ATIS	DENVER APP CON	DENVER TOWER	GND CON
125.6 379.9	119.3 307.3 (N) 120.35 379.3 (S)	124.3 322.45	121.35 379.175 (W) 121.85 377.1 (E)



ELEV 5434 D TDZE 5434

HIRL all rwys

TDZL/RCLS rwys 7, 16L, 16R, 17R, 26, 34L, 34R, 35L, 35R





CATEGORY	A	B	C	D
LPV DA	5634/18 200 (200-½)			
LNAV/VNAV DA	5684/24 250 (300-½)			
LNAV MDA	5780/24 346 (400-½)		5780/30 346 (400-⅝)	

SW-1, 29 OCT 2026 to 26 NOV 2026
SW-1, 29 OCT 2026 to 26 NOV 2026