

WAAS CH <b>40019</b>	APP CRS <b>225°</b>	Rwy ldg TDZE Apt Elev	<b>8655</b> <b>13</b> <b>13</b>
-------------------------	------------------------	-----------------------------	---------------------------------------

**RNAV (GPS) RWY 22R**  
NEW YORK / JOHN F. KENNEDY INTL (JFK)

**▼** DME/DME RNP -0.3 NA. Baro-VNAV NA below -15°C (5°F). Simultaneous approach authorized with ILS or LOC Rwy 22L, ILS Rwy 22L (CAT II), ILS Rwy 22L (CAT III), RNAV (GPS) Y Rwy 22L. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

**MISSED APPROACH:** Climb to 4000 direct PIDTO and right turn via 237° track to COL VOR/DME and hold.

ATIS (ARR-NE) (ARR-SW)	NEW YORK APP CON	KENNEDY TOWER Rwys 4R/22L and 13L/31R Rwys 4L/22R and 13R/31L	GND CON	CLNC DEL
<b>128.725 117.7 115.4</b>	<b>127.4 269.0</b>	<b>119.1 281.55</b> <b>123.9 281.55</b>	<b>121.9</b> <b>348.6</b>	<b>135.05</b> <b>348.6</b>

