


WAAS CH 40019 W22B	APP CRS 225°	Rwy ldg THRE 13 Apt Elev 14
--	------------------------	---

RNAV (GPS) RWY 22R
NEW YORK / JOHN F. KENNEDY INTL (JFK)


▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized with ILS or LOC Rwy 22L, ILS Rwy 22L (CAT II), ILS Rwy 22L (CAT III), RNAV (GPS) Y Rwy 22L. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MISSED APPROACH: Climb to 4000 direct PIDTO and right turn on track 237° to COL VOR/DME and hold.

ATIS (ARR-NE) (ARR-SW) 128.725 117.7 115.4	NEW YORK APP CON 127.4 269.0	KENNEDY TOWER Rwys 4R/22L and 13L/31R 119.1 281.55 Rwys 4L/22R and 13R/31L 123.9 281.55	GND CON 121.9 135.05 348.6	CLNC DEL 135.05 348.6
---	--	---	--	---



ELEV 14	D	THRE 13
---------	----------	---------



RLLS Rwy 13R
HIRL all Rwys
TDZ/CL Rwys 4R, 13L, 31R and 22L

4000	PIDTO	COL
↑	✱	↪ tr 237°
*LNAV only.		
*1.7 NM to RWY 22R		
RWY 22R		
HENEB		
RVRIA		
2500		
GS 3.00° TCH 59		
CATEGORY	A	B
LPV DA	270/40	257 (300-¾)
LNAV/VNAV DA	480-1½	467 (500-1½)
LNAV MDA	600/50	587 (600-1)
CIRCLING	640-1	626 (700-1)