

WAAS CH 97318 W22A	APP CRS 224°	Rwy Idg TDZE Apt Elev	8400 12 13
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) Y RWY 22L

JOHN F KENNEDY INTL (JFK)

RNP APCH.

Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000.

ALS F-2

MISSED APPROACH: Climb to 3000 direct FOLER and on track 188° to CHANT and hold.

D-ATIS (ARR/DEP) (ARR-NE) (ARR-SW)			NEW YORK APP CON		KENNEDY TOWER		GND CON	CLNC DEL	CPDLC
128.725	117.7	115.4	128.125	269.0	Rwys 4R/22L and 13L/31R Rwys 4L/22R and 13R/31L	119.1 281.55 123.9 281.55	121.9 348.6	135.05 348.6	

3000	FOLER	tr 188°	CHANT	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 66).			
*LNAV only.				ZALPO	1800	224°	NAYIK
*1.5 NM to RWY 22L				RWY 22L	1800	224°	2000
1.5				4 NM	5.9 NM		GP 3.00° TCH 53
CATEGORY	A		B		C		D
LPV DA	269/18		257 (300-½)				
LNAV/VNAV DA	419/50		407 (500-1)				
LNAV MDA	560/24 548 (600-½)		560/60 548 (600-1¼)				
CIRCLING	640-1 627 (700-1)		680-1¾ 667 (700-1¾)		680-2 667 (700-2)		

NEW YORK, NEW YORK

Amtd 1F 21MAY20

40°38'N-73°47'W

JOHN F KENNEDY INTL (JFK)

RNAV (GPS) Y RWY 22L